

AVO UNIVERSAL TWIN-TUBE

We believe that we have the most comprehensive range of twin-tube telescopic and coil-over

- Steel or alloy construction.
- Single adjustable or independent double adjustable damping rate.
- Accept 1.9 or 2.25 l/d coil springs.
- Small 1 5/8" o/d or 2" o/d bodies (telescopic only).
- Poly bush or spherical bearing mounts.
- Open lengths from 9" - 20" available from stock.
- Specials built to order.

To find your damper, take the part number from the coil over damper options table or the telescopic damper options table, and add the part number from the dimensions table.

Example: "PA090/070" is a 1.625" steel bodied, 9" open, 7" closed coil over single adjustable damper, for 1.9" diameter springs which has poly bush mounts

Coil Over Damper Options										
To view the damper drawing goto the Downloads page			Poly Bush				Spherical Bearing Mounts			
			Single Adjustable		Double Adjustable		Single Adjustable		Double Adjustable	
Body Dia.	Spring ID	Construction	Part No.	Price	Part No.	Price	Part No.	Price	Part No.	Price
1.625"	1.9"	Steel	(PA)	£80.00	(DASPA)	£130.00	(WA)	£95.00	(DASWA)	£145.00
1.625"	1.9"	Aluminium	(APA)	£100.00	(DAAPA)	£150.00	(AWA)	£115.00	(DAAWA)	£165.00
2"	2.25"	Steel	(PF)	£90.00	(DASPF)	£165.00	(WD)	£105.00	(DASWD)	£180.00
2"	2.25"	Aluminium	(APF)	£115.00	(DAAPF)	£185.00	(AWD)	£130.00	(DAAWD)	£200.00

Coil Over Damper Options									
To view the damper drawing goto the Downloads page		Poly Bush				Spherical Bearing Mounts			
		Single Adjustable		Double Adjustable		Single Adjustable		Double Adjustable	
Body Dia.	Construction	Part No.	Price	Part No.	Price	Part No.	Price	Part No.	Price
1.625"	Steel	(TA)	£60.00	(DASTA)	£110.00	(BA)	£75.00	(DASBA)	£125.00
1.625"	Aluminium	(ATA)	£80.00	(DAATA)	£135.00	(ABA)	£95.00	(DAABA)	£150.00
2"	Steel	(TG)	£70.00	(DASTG)	£120.00	(BG)	£85.00	(DASBG)	£135.00
2"	Aluminium	(ATG)	£90.00	(DAATG)	£165.00	(ABG)	£105.00	(DAABG)	£180.00

AVO UK LTD

Performance Suspension

Damper Dimensions					
Open length	Closed length	Body length	Suggested spring length		Part No.
			1.9 I/D spring	2.25 I/D spring	
* 9"	7"	4"	N/A	5"	(090/070)
10"	7.5"	4.5"	5	6"	(100/075)
11"	8"	5"	6	7"	(110/080)
12"	8.5"	5.5"	7	8"	(120/085)
13"	9"	6"	7	8	(130/090)
14"	9.5"	6.5"	8	9"	(140/095)
15"	10"	7"	8	9"	(150/100)
16"	10.5"	7.5"	9	10"	(160/105)
17"	11"	8"	10	12"	(170/110)
18"	11.5"	8.5"	12	14"	(180/115)
19"	12"	9"	12	14"	(190/120)
20"	12.5"	9.5"	12	14"	(200/125)

* 9" Not available in Double adjustable.